# PARATHOM PRO CLASSIC P 4 W/827 E14

# PARATHOM LEDOTRON CLASSIC P | LED retrofit lamps



#### Areas of application

- All domestic rooms, especially where the lamps are visible
- Dimmable installations
- Wherever compact and efficient lamps are needed
- Where the lamps need to last a long time or have to withstand frequent on/off switching

#### **Product benefits**

- Comfortable digital dimming with LEDOTRON technology
- Full compatibility of lamp and control unit
- Flickerfree starting and flickerfree operation
- Contains no mercury

#### **Product features**

- Dimmable (1...100 %)
- Lifetime: up to 25,000 h
- Color temperature: 2,700 K







#### Technical data

### **Electrical data**

| Rated wattage                          | 4.00 W   |
|--|----------|
| Nominal wattage                        | 4.00 W   |
| Nominal voltage                        | 220240 V |
| Operating frequency                    | 5060 Hz  |
| Power factor λ                         | 0.50     |
| Claimed equiv. conventional lamp power | 25 W     |


### Photometrical data

| Color temperature                    | 2700 K     |
|--------------------------------------|------------|
| Color rendering index Ra             | 80         |
| Light color (designation)            | Warm White |
| Standard deviation of color matching | ≤6 sdcm    |
| Nominal luminous flux                | 250 lm     |

# Light technical data

| Starting time 0.5 s |  |
|---------------------|--|
|---------------------|--|

# Dimensions & weight



| Overall length | 82.0 mm |
|----------------|---------|
| Length         | 82.0 mm |
| Diameter       | 43.0 mm |

## Lifespan

| Nominal lamp life time     | 25000 h |
|----------------------------|---------|
| Rated lamp life time       | 25000 h |
| Number of switching cycles | 100000  |

| Lumen maintenance at end of service life | 0.70 |
|--|------|

### Additional product data

| Base (standard designation) | E14   |
|-----------------------------|---|
| Mercury-free                | Yes   |
| Product remark              | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/In development, data preliminary |

### **Capabilities**

| Dimmable | Yes <sup>1)</sup> |
|----------|-------------------|
|----------|-------------------|

 $<sup>^{1)}</sup>$  LEDOTRON only

#### Certificates & standards

| Energy efficiency class | A+          |
|-------------------------|-------------|
| Energy consumption      | 4 kWh/1000h |

### **Country specific categorizations**

| ILCOS           | DRBP/F-4/827-230-E14-43 |  |
|-----------------|-------------------------|--|
| Order reference | PARACLP25LED 4W         |  |

#### Equipment / Accessories

- Suitable for dimming with LEDOTRON control devices only

### Logistical Data

| Product code  | Product description                      | Packaging unit<br>(Pieces/Unit) | Dimensions (length x width x height) | Volume               | Gross weight |
|---------------|--|---------------------------------|--------------------------------------|----------------------|--------------|
| 4052899914742 | PARATHOM PRO<br>CLASSIC P 4 W/827<br>E14 | Shipping carton box<br>10       | 248 mm x 106 mm x<br>102 mm          | 2.68 dm <sup>3</sup> | 800.00 g     |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### References / Links

For Guarantee see

www.osram.com/guarantee

For further information please visit the LEDOTRON website:

www.ledotron.com

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.